

MATERIAL SAFETY DATA SHEET	
MFG. BY: SAFE ENCASEMENT SYSTEMS EMERGENCY CONTACT: (651) 454-4107 ADDRESS: 4491 Oak Chase Lane Eagan, MN 55123 Revised: September 2007 Information. Phone: (651) 454-4107_	SPECIAL FIRE FIGHTING PROCEDURES: For fires with this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus, to protect against the hazardous effects of normal products of combustion.
SECTION I - PRODUCT ID._	SECTION V - REACTIVITY DATA
PRODUCT NUMBER: SE-110-MS PRODUCT NAME: Multi-Surface Penetrating-Stabilizer (Primer with Corrosion Inhibitors) PRODUCT CLASS: Specialty Acrylic Primer Coating _	STABILITY: Stable (slight ammonia odor). CONDITIONS TO AVOID: Keep from freezing. INCOMPATIBILITY (MATERIALS TO AVOID): None reasonably foreseeable. Hazardous Polymerization: Will not occur HAZARDOUS DECOMPOSITION OR BY PRODUCTS: Will not occur.
SECTION II - HAZARDOUS INGREDIENTS_	SECTION VI HEALTH HAZARD DATA
None known at a hazardous level (slight ammonia odor, contains less than Windex Glass Cleaner). HMIS Hazard Ratings = 0 0 0 J This product contains no heavy metals or fibers. _	EFFECTS OF OVEREXPOSURE: INHALATION: inhaled mist can cause head aches, nausea or irritation of the nose, throat and lungs. EYE CONTACT: slightly irritating to eyes. SKIN EXPOSURE: irritating to skin upon prolonged or repeated contact. EMERGENCY AND FIRST AID PROCEDURES: For inhalation, move subject to fresh air. For eye contact, flush with large amounts of water for at least 15 minutes. See a physician if irritation persists. Wash effected skin area with soap and water. If swallowed, dilute by giving 2 glasses of water to drink and CALL A PHYSICIAN IMMEDIATELY. Never give anything by mouth to an unconscious subject. OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS_	SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE
APPEARANCE: Milky white liquid (dries clear) BOILING POINT: 100°C (212°F) Specific Gravity: Greater than 1.0 (H ₂ O = 1.0) VAPOR PRESSURE: (mm Hg @ 20°C) = 18 VAPOR DENSITY: lighter than 1.0 EVAPORATIVE RATE: equal to water PERCENT VOLATILE (by volume) = 50 - 55%_	STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep Spectators away. wear skin, eye and Respiratory Protection during cleanup. Dike and contain with inert absorbent materials (sand, earth, etc.). Transfer to containers for recovery or disposal.
SECTION IV - FIRE & EXPLOSION HAZARD DATA_	SECTION VIII - CONTROL MEASURES.
FLAMMABILITY CLASSIFICATION: DOT - NOT REGULATED. _	VENTILATION: GENERAL VENTILATION IS RECOMMENDED DURING NORMAL USE. LOCAL VENTILATION MAY BE REQUIRED DURING CERTAIN OPERATIONS TO PREVENT INHALATION OF VAPORS. RESPIRATORY PROTECTION: Wear respirator (MSHA or NIOSH Approved or equal) ORGANIC VAPOR/PARTICULATE RESPIRATOR. in case of poor ventilation or exposure to spray mist, use NIOSH APPROVED Organic Vapor Mask. PROTECTIVE GLOVES: IMPERVIOUS GLOVES FOR PROLONGED OR REPEATED CONTACT. EYE PROTECTION: CHEMICAL SPLASH GOGGLES (ANSI 2-87.1) or EQUIVALENT. OTHER PROTECTIVE EQUIPMENT AND MEASURES: UNHINDERED ACCESS TO SAFETY SHOWER AND EYE WASH STATIONS. AS A GENERAL HYGIENIC PRACTICE, WASH HANDS AND FACE AFTER USE. Showers and cleaning of clothes are recommended. Use approved clothing when working around asbestos or lead.
FLASH POINT - N/A LEL - N/A EXTINGUISHING MEDIA: N/A UNUSUAL FIRE & EXPLOSION HAZARDS: Material can splatter above 212°F. Polymer film can burn.	SECTION IX - REGULATORY INFO.
	DOT PROPER SHIPPING NAME: Not Regulated. Follow all applicable OSHA and EPA regulations concerning normal latex spraying activities.