

MATERIAL SAFETY DATA SHEET		<p>SPECIAL FIRE FIGHTING PROCEDURES: For fires with this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus, to protect against the hazardous effects of normal products of combustion.</p>	<p>Floors may be slippery, use care to avoid falls. Flush final traces with water. Keep spills and cleaning run-off materials out of municipal sewers or open bodies of water.</p>
<p>MFG. BY: SAFE ENCASEMENT SYSTEMS EMERGENCY CONTACT: (651) 454-4107 ADDRESS: 4491 Oak Chase Lane Eagan, MN 55123</p> <p>Revised: September 2007 Information. Phone: (651) 454-4107</p>		<p>SECTION V - REACTIVITY DATA</p>	<p>WASTE DISPOSAL METHOD: Disposal should be in accordance with Federal, state and local regulations for water-based coatings. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Incinerate the solids and contaminated diking material at a permitted facility, according to Federal, State and local regulations.</p>
SECTION I - PRODUCT ID.		<p>STABILITY: Stable. CONDITIONS TO AVOID: <i>Keep from freezing.</i> INCOMPATIBILITY (MATERIALS TO AVOID): None reasonably foreseeable. HAZARDOUS POLYMERIZATION: Will not occur HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Will not occur.</p>	<p>PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: <i>KEEP FROM FREEZING.</i></p>
<p>PRODUCT NUMBER: SE-130 PRODUCT NAME: Protective-Skin PRODUCT CLASS: Acrylic Elastomeric Coating.</p>		SECTION VI - HEALTH HAZARD DATA	SECTION VIII - CONTROL MEASURES.
SECTION II - HAZARDOUS INGREDIENTS		<p>EFFECTS OF OVEREXPOSURE: INHALATION of excessive vapor/mist can cause headache, nausea and irritation of the nose, throat and lungs. EYE CONTACT: slightly irritating to eyes. SKIN EXPOSURE: irritating to skin upon prolonged or repeated contact.</p>	<p>VENTILATION: GENERAL VENTILATION IS RECOMMENDED DURING NORMAL USE. LOCAL VENTILATION MAY BE REQUIRED DURING CERTAIN OPERATIONS TO PREVENT INHALATION OF VAPORS.</p>
<p>No Hazardous Ingredients. HMIS Hazard Rating = 0 0 0 J This product contains no heavy metals or fibers.</p>		<p>EMERGENCY AND FIRST AID PROCEDURES: For inhalation, move subject to fresh air. For eye contact, flush with large amounts of water for at least 15 minutes. See a physician if irritation persists. Wash effected skin area with soap and water. If swallowed, dilute by giving 2 glasses of water to drink and CALL A PHYSICIAN IMMEDIATELY. Never give anything by mouth to an unconscious subject.</p>	<p>RESPIRATORY PROTECTION: Wear respirator (MSHA or NIOSH APPROVED or the equivalent) ORGANIC VAPOR/PARTICULATE RESPIRATOR. IN CASE OF POOR VENTILATION (or exposure to spray mist), USE NIOSH APPROVED ORGANIC VAPOR MASK.</p>
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS		<p>OTHER PRECAUTIONS: <i>KEEP CONTAINERS TIGHTLY CLOSED. DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.</i></p>	<p>PROTECTIVE GLOVES: IMPERVIOUS GLOVES FOR PROLONGED OR REPEATED CONTACT.</p>
<p>APPEARANCE: COLORED LIQUID Weight per gallon: 12.97 pounds BOILING POINT: 100°C (212°F) SPECIFIC GRAVITY: 1.5 (H₂₀ = 1.0) VAPOR DENSITY: Lighter than Air EVAPORATIVE RATE: Slower than Ether VOC: 0.30 lbs. per gallon (36 G/L) PERCENT VOLATILE (by volume): 50%</p>		SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE.	<p>EYE PROTECTION: CHEMICAL SPLASH GOGGLES (ANSI 2-87.1) or EQUIVALENT.</p>
SECTION IV - FIRE & EXPLOSION HAZARD DATA		<p>STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep Spectators away. WEAR SKIN, EYE, AND RESPIRATORY PROTECTION DURING CLEANUP. Dike and contain with inert absorbent materials (sand, earth, etc.). Transfer to containers for recovery or disposal.</p>	<p>OTHER PROTECTIVE EQUIPMENT AND MEASURES: UNHINDERED ACCESS TO SAFETY SHOWER AND EYE WASH STATIONS. AS A GENERAL HYGIENIC PRACTICE, WASH HANDS AND FACE AFTER USE. Showers and cleaning of clothes are recommended. Use approved clothing when working around hazardous materials.</p>
<p>FLAMMABILITY CLASSIFICATION: DOT - NOT REGULATED. FLASH POINT – N/A LEL - N/A EXTINGUISHING MEDIA: CO₂, Water Fog UNUSUAL FIRE & EXPLOSION HAZARDS: Material can splatter above 212°F. Polymer film can burn.</p>			SECTION IX - REGULATORY INFO.
			<p>DOT PROPER SHIPPING NAME: Not Regulated. Follow all applicable OSHA and EPA regulations concerning normal latex spraying activities.</p>